

IL Series Infrared Laser Module



Part No: IL-8508-**XXX-XX-X**

XXX(Wavelength): 780, 808, 850, 980.

XX(Output Power): 1, 5, 10.....

X (Lens): G, P. (G-GLASS, P-PMMA)




Specification:

Wavelength (λ)	: 780nm, 808nm, 850nm, 980nm.
Operating Voltage (Vop)	: DC5V.
Operating current (Iop)	:
Optical Output Power (After Lens)	: 1mW, 3mW, 5mW, 7mW, 10mW, 15mW, 20mW, 30mW, 50mW, 80mW.
Lens	: PMMA (P), Glass (G)
Laser Pattern	: Point.
Laser Operation (Mode)	: Continuous (CW).
Laser Structure	: Single & Multi-mode Laser.
Power Stability	: <1%.
Wavelength Drift	: 0.2nm/°C.
Laser Class	: IIIA.
Control Circuit	: APC + Regulator.
Operating Temperature	: -10°C ~+50°C.
Storage Temperature	: -40°C ~+80°C.
Electrical Connections	: +Red, -Black.
Cable	: 22 cm.
Dimension	: 20 mm(D) X 50 mm(L)
Housing Material	: Copper + POM

Application:

- Measurement
- Bio-analytical
- Automation
- Alignment



Operational Hazard-Semiconductor Laser Diode Module:

This laser module emits radiation that is visible and harmful to human eye. When in use, do not look directly into the laser emitting aperture. Direct viewing of laser diode emission at close range may cause eye damage.

Limited Warranty: One year. No warranty coverage for disassembly, modifications or damage due to abuse or misapplication.

E-Laser Enterprise Co., Ltd

No 398, Jinghe E. Rd., Beitun District, 406 Taichung City, Taiwan.

Tel: 886-4-2436-9426 Fax: 886-4-2436-5843

E-Mail: laser.ling@msa.hinet.net

<http://www.linelaser.com.tw/>